

Non Structural Repair Material

INCAP PATCH

INCAP PATCH is a thick repair mortar for the patching and resurfacing of deteriorated masonry structure. INCAP PATCH has been specifically formulated to produce superior bond, low shrinkage, chemical durability and high strength. It is a one component mortar and can be either sprayed or trowel applied at a thickness of 3/8 in. to 2 in. (10 mm to 50 mm). The high performance characteristics of INCAP PATCH are enhanced by TECHNOKOTES's unique crystalline waterproofing and protection technology.

Benefits

- Excellent adhesion and bond to masonry substrates
- Low shrinkage, can be fibre reinforced
- Low chloride penetration
- Ready to use – just add water
- Vertical and overhead concrete repair; spray able
- VOC compliant

Applications

- Water Tanks and Reservoirs
- Sewage Treatment Plants
- Concrete Water and Sewer Pipes
- Manholes and Vaults
- Marine Structures
- Bridge Structures
- Tunnels and Parking Garages



Urmi Aangan, Pedder Road



Plaza Theatre, Dadar



INCAP PATCH for cement bricks

Note

- In hot, dry, windy weather, special curing procedures may be required prior to final set. This may involve use of fog spray, or suitable curing compounds following finishing.
- INCAP PATCH should not be mixed and placed at temperatures below 3°C or above 40°C. Protect from rapid evaporation (hot and/or cold and windy conditions).
- For rehabilitation applications, where a thin parge coating (less than 3/8 in. or 10 mm) or a cap coat for INTONACO is required, call Technical Service Team.