

SPECIALITY PRODUCTS

INCRETE INTANACO

INCRETE INTANACO is a ready to use mineral render mortar for internal and external application on traditional masonry bricks, blocks or concrete, either new or existing. Application allows protection and levelling of treated supports whilst maintaining masonry breathability. INCRETE INTANACO can be advantageously used to replace cement-lime mortar made on site, for internal and external plastering of traditional masonry. This product is designed to be applied by hand or mechanically sprayed with tradition plastering machines.

Benefits:

- No bulk mixing required, just add water and INCRETE INTONACO is ready to use.
- Considerably more economical than 15mm of standard cement render and can be applied in about half the time.
- Due to the polymer additives, INCRETE INTONACO has superior application and adhesion properties over sand/cement renders, guaranteed performance, including elimination of shrinkage and hair cracking.
- No need to transport bulk sand and cement to the job site.
- Packaged in convenient 25 kg bags. Only mix what you need. No Wastage.
- Also available: INCRETE INTONACO Fine for a gloss smooth finish.

Applications

Renovating brick, stone and tuff masonry, including recent builds, damaged by capillary rising damp. Renovating masonry damaged by the crumbling effect of sulphates, chlorides and nitrates.

Some application examples

- Internal and/or external macroporous, dehumidifying and insulating render on stone, brick, tuff and mixed masonry, including recent builds, with capillary rising damp and saline efflorescence.
- Dehumidifying and insulating render on stone (such as limestone) and/or particularly porous, absorbent brick masonry, and in general wherever there is saline efflorescence.
- Dehumidifying render for masonry in lagoon areas or close to the sea.
- Repairing damaged render on buildings built using low performance mortar.
- Pointing between stone, brick and tuff elements on "exposed" masonry