

ULTRA TOPKOTE

ULTRA TOPKOTE is a high strength, self levelling concrete overlay topping that is easy to place. ULTRA TOPKOTE rapidly gains strength to allow pedestrian and vehicle traffic or mechanical polishing within 24 hours after placement. The time-proven benefits of positive bonding and durability assure precise decorative repair of worn and pitted concrete surfaces.

ULTRA TOPKOTE quickly develops strength and can be dyed with provided dyes and polished with concrete polishing systems, if desired. This attractive, fast curing, fibre reinforced, self-levelling material may be placed in various thicknesses from 10-50mm depth in a single pour. ULTRA TOPKOTE can be integrally coloured for additional decorative effect.

Uses

The rapid strength, self-levelling features of ULTRA TOPKOTE assure an attractive durable concrete repair surface for worn, uneven and pitted existing concrete floors. Its excellent workability and wear resistance make it ideal for patch repairs in large and small areas that require a very durable and polishable repair material. Use ULTRA TOPKOTE to renovate and correct irregularities in uneven and worn structural floors, including light manufacturing, malls, retail stores, warehouses and lobbies.

Advantages

- Long flow life
- Polishable topping within 24 hours
- High abrasion resistance
- Can be dyed or coloured
- Rapid strength gain
- Excellent bonding to sound concrete surface
- Single applications 10-50 mm
- Can add decorative aggregate

