

## SEALKOTE CRACK

SEALKOTE CRACK is a black, rubberized single component cold applied viscous liquid. It's heavy and slow curing, filling up 4mm and wider cracks. SEALKOTE CRACK, sealer prevents water penetration into the crack, and adheres with the surrounding pavement.

### Benefits

- Revolutionary cold application crack repair, ideal for places where hot application is too dangerous (e.g. airports)
- Cheap and long lasting
- Manual or automated application possible, no heating required

### Applications

SEALKOTE CRACK is mainly used for sealing moving minor cracks.

#### Note:

*SEALKOTE CRACK is intended for sealing various types of asphalt/concrete cracks. Narrower cracks can be sealed by coating the whole surface with a thin membrane of SEALKOTE SB, and wider ones require deep patching by using SEALKOTE PATCH, pothole sealing materials but the vibrating cracks require a rubberized solution.*

## SEALKOTE M

A single component transparent polymer, SEALKOTE M is a durable, all-weather hydrophobic paint coating. Just like any other paint, HL is very easy to apply and requires no special machinery. However, once cured it demonstrates excellent protective characteristics reducing negative weather effects, UV rays or chemical damages.

### Benefits

- Certified and patent (applied for)
- Resistant to humidity, temperature, UV rays, chemicals and more
- Works well both indoors and out
- Fast curing, even under extreme sub-zero temperatures

### Applications

The SEALKOTE M paint is used in various types of applications, ranging from

- Steel pipes sealing
- Anti-corrosion to gas insulation
- Residential complexes.